

AM73915MZT



The Dino-Lite AM73915MZT is part of the High Speed range with USB 3.0 connection. It offers superb uncompressed image quality and color reproduction in a robust, compact and appealing metal housing.



USB 3.0



HIGH SPEED



ADJUSTABLE
~10-220x



MAGNIFICATION
LOCK



5 MEGAPIXEL
2592 x 1944



8 WHITE LEDs
SWITCHABLE



POLARIZER
ANTI-REFLECTION



STANDARD
WORKING
DISTANCE

USB 3.0 adds a new transfer mode called "SuperSpeed" (SS) capable of transferring data up to 5Gbits/s (625MB/s). Dino-Lite models with USB 3.0 offer an image transfer speed of up to 45FPS at a 1280 x 960 resolution. SuperSpeed allows you to take advantage of the full power of the Dino-Lite Edge Series optics including improved colour accuracy and image quality.

The Dino-Lite AM73915MZT is a USB 3.0 model with a magnification range of 10x - 220x and a standard working distance of up to 6 cm. This model is member of the Dino-Lite Edge family with the latest, cutting-edge optics, an unmatched 5 megapixel sensor and several special features such as the Extended Depth of Field (EDOF), Enhanced Dynamic Range (EDR), Automatic Magnification Reading (AMR), Flexible LED Control (FLC), built-in polarization filter, full metal body, extensive measurement functions, calibration, exchangeable front caps and more.

EDOF allows users to automatically capture multiple images at different depths and automatically

combine them into one clear image. EDR automatically captures and combines multiple images at different exposure levels to produce a final image with greater dynamic range. The AMR function automatically detects and displays the magnification of the Dino-Lite. The magnification is displayed within the Dino-Lite software and stored with the captured picture and simplifies the measuring process.

The AM73915MZT is one of the most high-end Dino-Lite products available and the top-level product within the Dino-Lite USB 3.0 range. For professionals who are looking for high speed data transfer, the best available image quality and are looking for advanced features this is the model of choice.

**EDOF/EDR only functions under Windows OS*

Additional Info

- Dino-Lite Range: Dino-Lite High Speed
- Resolution: High (5 Megapixel)
- Magnification: Standard (10x - 220x)
- Interface: USB 3.0 Cable included
- Working Distance: Standard
- Price Range (excl. VAT): €1000,00 - €1250,00
- Light/ LED type: White
- ESD Safe: Yes
- Polarizer: Yes
- Housing: Metal housing
- Special feature: Aut. Magn. reading, Ext. Dynamic Range (EDR), Ext. Depth of Field (EDOF), Flexible LED Control (FLC)
- Dino-Lite Range: Dino-Lite High Speed
- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: Yes
- Emission filter: No
- Polarizer: Yes, linear
- Magnification: 10-220x
- Macro zoom: No
- Working Distance: Standard
- Resolution: 5 Megapixel (2592x1944)
- Maximum Frame rate: 45 fps
- Interface: USB 3.0, Cable included
- Housing material: Metal housing
- Magnification lock: Yes
- Measurement: Yes
- Calibration: Yes
- Microtouch sensor: Yes
- ESD Safe: Yes
- Special feature: Aut. Magn. reading, Ext. Dynamic Range (EDR), Ext. Depth of Field (EDOF), Flexible LED Control (FLC)

- Package contents: Microscope, Carry pouch, Software CD, User manual, Quick guide, Calibration target, Front cover box
- Price Range: €1000,00 - €1250,00

- **Details**

- Dino-Lite range: Dino-Lite High Speed

- **Lighting**

- Light/ LED type: White
- Number of LEDs: 8
- LED on/off switchable: Yes
- Infrared filter: IR cut-filter >650 nm
- Diffuser available: Yes (N3C-D included)
- Emission filter: No
- Polarizer: Yes, linear

- **Optics**

- Magnification: 10-220x
- Macro zoom: No
- Working distance: Standard
- Lens type: Glass with anti-reflection coating

- **Sensor**

- Sensor type: CMOS
- Resolution: 5 Megapixel (2592x1944)
- Maximum frame rate: 45 fps

- **Compatibility**

- Interface: USB 3.0, Cable included**
- Operating system: Windows 7, 8 & 10, MacOS 10.9 and up
- Included software: DinoCapture 2.0 (Windows), DinoXcope (Mac OS)
- Supported image formats (Windows): BMP, GIF, PNG, JPG, TIF, RAS, PNM, TGA, PCX, MNG, WBMP, JP2, JPC, PGX
- Supported video formats (Windows): WMV, FLV, SWF
- Supported image formats (MacOS): JPEG, PNG
- Supported video formats (MacOS): MOV
- Imaging standards: DirectShow, UVC

- **Housing**

- Housing material: Metal housing
- Magnification lock: Yes
- Dimensions: 11.9cm (L) x 3.3cm (H)
- Weight: 110g
- Cable length: 1.8m

• Features

- Special feature: Aut. Magn. reading, Ext. Dynamic Range (EDR), Ext. Depth of Field (EDOF), Flexible LED Control (FLC)
- Measurement: Yes
- Calibration: Yes
- Microtouch sensor: Yes
- ESD safe: Yes

• Information

- Package contents: Microscope, Carry pouch, Software CD, User manual, Quick guide, Calibration target, Front cover box
- Warranty information: 2 years European warranty
- Regulatory approval: CE, FCC, ROHS
- Price range: €1000,00 - €1250,00
- Working distance/ field of view/ depth of field:

Magnification Rate	Working Distance ⁸	Field of View(x)	Field of View(y)	Depth of Field
10	136.0	37.8	28.3	-
20	60.2	19.5	14.6	2.5
30	33.5	13.0	9.7	1.8
40	20.9	9.8	7.3	1.5
50	13.9	7.8	5.8	-
60	9.7	6.5	4.8	-
70	7.1	5.6	4.2	1
80	5.5	4.9	3.6	-
90	4.5	4.3	3.2	-
100	4.1	3.9	2.9	-
110	4	3.6	2.7	-
120	4.1	3.3	2.4	-
130	4.5	3.0	2.2	-
140	5	2.8	2.1	-
150	5.6	2.6	1.9	-
160	6.3	2.4	1.8	-
170	7.1	2.3	1.7	-
180	8	2.2	1.6	-
190	8.9	2.1	1.5	-
200	9.9	2.0	1.5	-
210	10.9	1.9	1.4	-
Listed values may differ slightly	*Without front cap			Unit = mm

Magnification Rate	Working Distance8	Field of View(x)	Field of View(y)	Depth of Field
220	11.9	1.8	1.3	0.1
Listed values may differ slightly	*Without front cap			Unit = mm

**Dino-Lite USB 3.0 models use a custom USB cable that is specifically designed for Dino-Lite

PDF generated on: 31-05-2018