CS glass measuring rods





Table of contents

The classic instrument for length measurement 2


Specifications 2


CS glass measuring rods

The classic instrument for length measurement



These precision glass measuring rods have graduations and numbers consisting of vapour-coated hard chrome. One scale each available in metric and inch increments. A white strip serves as a background on one side of the numbers to allow them to be read off more easily. The chrome scales are equipped with two anodised grips on the sides for secure handling. The precision magnifiers (type 2016 with 15x magnification factors and 12 millimetre field of vision) in combination with the two lights. ensure simple, error-free read-off of the scale. The smallest increment on the inch scale is 0.005". The minimum increments on the metric scale are 0.1 millimetre. A further increase in the read-off accuracy is possible with the chrome micro-scale. Here an adapted analogue or digital dial gauge allows measurement of the distance between the one-tenth graduations. This allows precise measurements right down to one one-hundredth of a millimetre.





These valuable precision glass measuring rods are delivered in a stable wooden case to protect them from damage. These chrome scale rods are available in lengths of 300, 500, 800, 1000, 1400, 1600 and 2000 millimetres. Special lengths available on request. These glass measuring rods have the advantage that their expansion is minimal when heated. Temperature variations therefore have hardly any effect when using chrome scale rods.

Specifications

- Upper measuring scale: Increments = 0.005"
  labelling (small) 0 .05 .10 ... (inches)
  labelling (large) 0 1.0 2.0 ... (inches)
- Lower measuring scale: Increments = 0.1 mm
  labelling (small) 0 .1 .2 ... (mm)
  labelling (large) 0 10 20 ... (mm)
- The graduations and numbers are vapour-coated with hard chrome on the glass rods are high resolution and absolutely scratch resistant. The graduations have a thickness of 0.010 mm
- The white strips facilitate reading in dark areas.
- Increment accuracy in compliance with DIN 864:
  ± (0.003 mm + 3L / 1'000'000)
  Example: L = 500 mm, graduation error <= 0.0045 mm (dimensions based on 20°C)
- Thermal coefficient of expansion: 9 x 10-6 / °C.
- Refraction index = 1.5195
- Material = float glass (selected)
- Scaling not centred / centred on glass element! (multiple use)
- Length of glass elements = nominal length in inches x 25.4 mm / inches + 49 mm
- Width of glass element = 39 mm
- Thickness of glass element = 6 mm
- Available in lengths of (measuring range on double scale):

300 mm / 12"	= Gesamtlänge	353.8 mm (± 1mm)
500 mm / 20"	= Gesamtlänge	557.0 mm (± 1mm)
800 mm / 32"	= Gesamtlänge	861.8 mm (± 1mm)
1,000 mm / 40"	= Gesamtlänge	1,065.0 mm (± 1mm)
1,400 mm / 56"	= Gesamtlänge	1,471.4 mm (± 1mm)
1,600 mm / 64"	= Gesamtlänge	1,674.6 mm (± 1mm)
2,000 mm / 80"	= Gesamtlänge	2,081.0 mm (± 1mm)

Back to table of contents

Order no.	Description	Price excl. VAT.
CS-300	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 300 mm	
CS-500	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 500 mm	
CS-800	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 800 mm	
CS-1000	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 1000 mm	
CS-1400	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 1400 mm	
CS-1600	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 1600 mm	
CS-2000	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 2000 mm	
CSM-300	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 300 mm and additional analogue dial gauge	
CSM-500	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 500 mm and additional analogue dial gauge	
CSM-800	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 800 mm and additional analogue dial gauge	
CSM-1000	Chrome glass measuring rod with 0.1mm and 0.005" graduations, incl. box - 1000 mm and additional analogue dial gauge	

Back to table of contents