

MOTICAM S Series

# MOTICAM S12





MOTICAM S Series

**MOTICAM S12**

<b>Sensor type</b>	sCMOS
<b>Sensor size</b>	1/1.7"
<b>Imaging area</b>	9.33mm (Diagonal)
<b>Capture resolution</b>	12MP
<b>Live display mode through USB</b>	4000x3000, 2048x1080 pixels
<b>Pixel size</b>	1.85x1.85µm
<b>Scan mode</b>	Progressive
<b>Shutter mode</b>	Rolling Shutter
<b>Data transfer</b>	USB 3.1
<b>Max. frames per second (fps*)</b>	4000x3000 @ 25fps, 2048x1080 @ 50fps
<b>Exposure time</b>	22 µsec to 2 sec
<b>Operating temperature</b>	From -10 to +60 Degrees Celsius non condensing
<b>Max. signal to noise ratio</b>	0.1mV @1/30 sec
<b>Sensitivity</b>	280mV(G) @ 1/30 sec
<b>Support device</b>	TWAIN, SDK and DirectShow Driver
<b>Supported OS</b>	Windows 7/8/10, MAC OSX, Linux or higher
<b>Minimum computer requirements</b>	2GHz dualcore - RAM memory 2GB - Video memory min. 512 MB
<b>Lens mount</b>	C-Mount
<b>Software</b>	Motic Images Plus 3.0 for Windows, OSX and Linux
<b>Functions</b>	Still image and video capture, live and still image measurement, image adjustments, white balance, automatic & manual exposure, individual objective calibration system.
<b>Power supply</b>	5V (From USB Port)
<b>Package includes</b>	CS ring adaptor, USB 3.1 cable, Motic 4-dot calibration slide, Motic Images Plus 3.0 for PC/OSX/Linux

\*Frames per second under optimal lighting conditions and in compliance with computer technical requirements.